## **SET PALACE**

**Cistern** 82870.0



160

150

## TECHNICAL DATA

Order no.	82870.0
Certified to	DIN 19542
matching for	Floorstanding WC pan
	order no. 82470.6 / Charge 000
Specification	Flushing mechanism Impuls 590, Charge 278
	water condensation insulation
	Dual-Flush (6/3-I-flush)
Special specification	Australian Standard, Charge 264
Water inlet	side left, side right (3/8"), rear (3/8"-1/2")
Weight	13,0 kg
Mounting acc. incl.	Corner valve for rear water inlet
Colours	see colour table

## SPECIFICATION TEXT

DIN 19542, dimensions 360 x 160 x 420 mm Dual-Flush 6/3-1 water inlet side left, side right (3/8"), rear (3/8"-1/2") matching floorstanding WC pan, order no. s2470.6/option 000 Special feature: water condensation insulation Further options: Surface refinement LCC (only white), Australian Standard option 264
water inlet side left, side right (3/8"), rear (3/8"-1/2") matching floorstanding WC pan, order no. s2470.6/option 000 Special feature: water condensation insulation Further options: Surface refinement LCC (only white), Australian Standard option 264
matching floorstanding WC pan, order no. 82470.6/option 000 Special feature: water condensation insulation Further options: Surface refinement LCC (only white), Australian Standard option 264
Special feature: water condensation insulation Further options: Surface refinement LCC (only white), Australian Standard option 264
Further options: Surface refinement LCC (only white), Australian Standard option 264
option 264
•
Order no. 82870.0

## TECHNICAL DRAWINGS / S 1 : 20

