

URINALS

Siphonic urinal CAPRINO PLUS

84206.5



TECHNICAL DATA

Order no.	84206.5
Certified to	EN 13407
Specification	1-l flushing electronic controlled siphonic urinal Electronic control 230 V only in combination with fixing set order no. 89280.8
Water inlet	concealed, 1/2"
Outlet	horizontal or vertical
Flushing	1 l
Flushing rate	minimum 0,3 l/s
Weight	20,0 kg
Mounting acc. incl.	Electronic control system 230 V with all mounting accessories Charge 000 – without fly, 1-litre siphon with horizontal and vertical outlet DN 40 (standard CH) Charge 400 – with fly, 1-litre siphon with hori- zontal and vertical outlet DN 40 (standard CH) Charge 401 – without fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) Charge 411 – with fly, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK)

Mounting acc. incl.	Charge 407 – without fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Charge 417 – with fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	Stone screw fixing set M8
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-CAPRINO PLUS, sanitary ceramic, electronic control
EN 13407, dimensions 320 x 350 x 645 mm
1-l flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing rate minimum 0,3 l/s
electronic control system 230 V with all mounting accessories, 1-litre siphon with horizontal and vertical outlet DN 50 (standard Europe, except CH and UK) and outlet DN 40 (standard CH), 2-litre siphon with horizontal outlet DN 40 (standard UK)
Special feature: Vacuum and performance tested
Further options: Surface refinement LCC (only white), with fly
Order no. 84206.5

TECHNICAL DRAWINGS / S 1 : 20

