

FRAME 25 MIRROR

Mirror without light element

44740.9

Light element for mirror

44754.1

44754.2

44757.1

44757.2



TECHNICAL DATA

| | | | |
|--------------------|--|----------------------|---|
| Order no. | 44740.9 / mirror 44754.1, 44757.1 / light element 44754.2, 44757.2 / light element with switch | Specification | LED light element vertical : fixation with integrated non hinge system 44757.1 – vertical, without switch 1x 12W, 4000 Kelvin (daylight), IP44, 230V 44757.2 – vertical, with sensor switch integrated in the mirror aluminium frame 1x 12W, 4000 Kelvin (daylight), IP44, 230V |
| Certified to | IP44 / 44754.1, 44754.2, 44757.1, 44757.2 | Weight | 44740.9 – 14,0 kg 44754.1, 44754.2 – 3,5 kg 44757.1, 44757.2 – 1,5 kg |
| Dimensions (WxHxD) | 1500 x 700 x 23 mm (+4 mm gap to wall) / mirror 1500 x 25 x 25 mm / light element horizontal 25 x 711 x 25 mm / light element vertical | Mounting acc. incl. | Installation set for mirror, order no. 49831.5 |
| Specification | Mirror without light: mirror glass 4 mm with security foil on the back side, integrated in aluminium frame electro polished LED light element horizontal: fixation with integrated non hinge system 44754.1 – without switch 1x 30W, 4000 Kelvin (daylight), IP44, 230V 44754.2 – with sensor switch integrated in the mirror aluminium frame (bottom side) 1x 30W, 4000 Kelvin (daylight), IP44, 230V | Mounting information | The fortification walls must meet the requirements of the furniture in terms of weight and the supplied fasteners. This can not be guaranteed, another method of attachment is chosen. 230V power supply required (only for mirror with light element). |

TECHNICAL DRAWINGS / S 1 : 20

