LEELO MIRROR

Mirror with LED lighting and ambient light 3 touch sensors


4**4761.3** 4**4762.3**





| TECHNICAL DATA | | |
|--------------------|--|--|
| Order no. | 44761.3 | |
| | 44762.3 | |
| Certified to | IP44 | |
| Energy label | A++ | |
| Dimensions (WxHxD) | see table and drawing below | |
| Specification | 3 touch sensors (on-off/dimming, colour | |
| | temperature change) with memory function, | |
| | last light state is remembered | |
| | Mirror glass 4 mm with security foil, integrated | |
| | in aluminum frame electro polished | |
| | With integrated horizontal LED lighting | |
| | With peripheral LED ambient lighting | |
| | 2700-6000 Kelvin (dynamic white, pre-sets 2700, | |
| | 4000, 6000 Kelvin), main light and ambient light | |
| | synchronized, IP44, 230V, 50/60 Hz | |

| Specification | Electrical power (W): | |
|----------------------|---|--|
| | 44761.3 - main light 5,1W / ambient light 21,3W | |
| | 44762.3 - main light 6,8W / ambient light 23,2W | |
| Weight | 44761.3 – 6,3 kg | |
| | 44762.3 – 7,5 kg | |
| Mounting acc. incl. | 2 installation sets, order no. 49621.9 | |
| | 1 installation set, order no. 49622.0 | |
| Mounting information | The fortification walls must meet the require | |
| | ments of the furniture in terms of weight | |
| | and the supplied fasteners. This can not be | |
| | guaranteed, another method of attachment | |
| | is chosen. | |
| | 230V power supply required. | |
| | | |

TECHNICAL DRAWINGS / S 1 : 20







| Order no. | A / mm | B/mm |
|-----------|--------|------|
| 44761.3 | 450 | 154 |
| 44762.3 | 550 | 254 |

