

Floorstanding cistern, two-part Universal for floorstanding WC pan
82966.1



TECHNICAL DATA

Order no.	82966.1
Certified to	EN 14055
matching for	Floorstanding WC pan Laufen Pro, order no. 82295.2 Palace, order no. 82370.1 Palomba Collection, order no. 82380.6 Floorstanding WC pan rimless Kartell by Laufen, order no. 82333.6, 82333.7 Laufen Pro, order no. 82295.6 Sonar, order no. 82334.1 The New Classic, order no. 82385.1
Specification	floorstanding, two-part Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,0 kg

Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Floorstanding cistern, two-part UNIVERSAL, sanitary ceramic EN 14055, dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 concealed water inlet top left rear, 1/2" brass
 matching floorstanding WC pan, Laufen Pro order no. 82295.2, Palace order no. 82370.1, Palomba Collection order no. 82380.6 and floorstanding WC pan rimless, Kartell by Laufen order no. 82333.6, 82333.7, Laufen Pro order no. 82295.6, Sonar order no. 82334.1, The New Classic order no. 82385.1
 Special feature: water condensation insulation
 Order no. 82966.1

TECHNICAL DRAWINGS / S 1 : 20

