

URINALS

Siphonic urinal ANTERO 84015.3



TECHNICAL DATA

Order no.	84015.3
Certified to	DIN 1390, EN 13407
Specification	0,5-l flushing siphonic urinal Ceramic siphon cover Siphon replaceable without dismantling urinal only in combination with fixing set order no. 89282.6 Charge 000 (DN 40) – without fly Charge 401 (DN 50) – without fly
Special specification	Charge 400 (DN 40) – with fly Charge 411 (DN 50) – with fly
Water inlet	concealed 1/2"
Outlet	horizontal
Flushing	minimum 0,5 l
Flushing rate	minimum 0,3 l/s
Weight	25,0 kg
Mounting acc. incl.	Ceramic siphon cover, order no. 89818.9 Wall fixing set M8 LAUFEN, order no. 89282.6 1-liter siphon, order no. 89419.3 Charge 000 – waste connection pipe DN 40, order no. 89419.4 Charge 401 – waste connection pipe DN 50, order no. 89419.5

Mounting acc. excl.	1-liter spare part siphon, order no. 89419.6 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-ANTERO, sanitary ceramic
DIN 1390, EN 13407, dimensions 380 x 365 x 770 mm
min. 0,5-l flush, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal, flushing rate minimum 0,3 l/s
siphon replaceable without dismantling urinal,
Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)
Further options / accessories: Surface refinement LCC (only white), with fly, 1-liter spare part siphon
Order no. 84015.3

TECHNICAL DRAWINGS / S 1 : 20

